

Sepam series 20

Ready-to-use configuration

Number of identical Sepam configurations ordered

This orderform can be used to define a complete Sepam configuration.
Check the boxes ☒ that match your choices.

Base unit, connectors and application

Base unit and UMI				Application	Type	Sensor							
Base unit with advanced UMI		S10UD	69807	Substation	S20	69820	CT	CT	L PCT				
UMI lead seal accessory 1		AMT852	69838		S2+	69773	CT	CT	L PCT				
(1) Cable used only with an advanced UMI.													
Base unit with basic UMI		S10UX	69803	Transformer	T20	69821	CT	CT	L PCT				
Remote advanced UMI module		DSM303	69803		T2+	69778	CT	CT	L PCT				
Connection cord		L = 0.6m	CCA770	Motor	M20	69822	CT	CT	L PCT				
		L = 2m	CCA772		B21	69824	VT						
		L = 4m	CCA774		B22	69826	PT						
Mounting plate		AMT840	69870					69830	69828	69831	69832		
Working language				CC A630							CC A634	CC A670	CC T640
Sepam series 20		EW / FR	69808										
		EW / ES	69811										
Connectors													
Type		Screw-type	CCA620	69883	Note: CCA930:3 phase CT CCA934:3 phase CT + I0								
		Ring-fing type	CCA622	69889									